



SIRIM QAS INTERNATIONAL SDN. BHD. (410334-X)

1, Persiaran Dato' Menteri, Seksyen 2, Peti Surat 7035, 40700 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel : 60-3-5544 6400 Faks : 60-3-5544 6797 www.sirim-qas.com.my

File No : P5-004530
Licence No : PT049504

Date : 01/12/2021

TONN CABLE SDN BHD
LOT 1 (PT 54), JALAN PERUSAHAAN 5
KAWASAN PERUSAHAAN BERANANG
43700 BERANANG
SELANGOR, MALAYSIA

Attn : MR. KHOO KHAI SIAN

Tel No : 03-87669888

Fax No : 03-87668111

Dear Sir/Madam,

Product Certification Licence

Product : FIRE RESISTANT CABLES
Standard : BS 6387 : 1994

With regards to your request for new/renewal/changes of licence(s) under the SIRIM Product Certification Licence scheme, enclosed please find the copy of the licence(s) and the certification report(s) for your safe keeping.

For enquiry, please contact

Officer Name : MUHAMAD ZULHANIZAM BIN IBRAHIM
Contact No : 603-55445191
Email : hanizam@sirim.my

Thank you.

This is a computer generated document. No signature is required.

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM

**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to**

**TONN CABLE SDN BHD
LOT 1 (PT 54), JALAN PERUSAHAAN 5
KAWASAN PERUSAHAAN BERANANG
43700 BERANANG
SELANGOR, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on**

FIRE RESISTANT CABLES

Please refer to detail in the SCHEDULE

**sebagai mematuhi keperluan
as complying with**

BS 6387 : 1994



Nur Fadhilah binti Muhammad
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.



SCHEDULE

TONN CABLE SDN BHD



Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, MINERAL FILLED LSHF INSULATED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10) SQ. MM. - CATEGORY CWZ
Rating	: 600/1000V
Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, XLPE-INSULATED, PVC-SHEATHED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630) SQ. MM. - CATEGORY CWZ
Rating	: 600/1000V
Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF-SHEATHED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630) SQ. MM. -
Rating	: 600/1000V
Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF SHEATHED, NON-ARMOURED, STRANDED PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM. - CATEGORY CWZ
Rating	: 600/1000V
Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF SHEATHED, ARMOURED, STRANDED PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM. - CATEGORY CWZ
Rating	: 600/1000V
Trade Mark	: TONN CABLE
Model	: MICA-LAYERED, XLPE INSULATED, PVC SHEATHED, NON-ARMOURED, STRANDED PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM. - CATEGORY CWZ
Rating	: 600/1000V

SCHEDULE

TONN CABLE SDN BHD



SIRIM

Trade Mark : TONN CABLE
Model : MICA-LAYERED, XLPE INSULATED, PVC SHEATHED, ARMOURED, STRANDED
PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5,
4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM. - CATEGORY CWZ
Rating : 600/1000V

Trade Mark : TONN CABLE
Model : MICA-LAYERED, PVC-INSULATED, NON-ARMOURED, SINGLE-CORE,
STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR(1.5, 2.5, 4, 6,
10, 16, 25, 35, 50, 70, 95) SQ. MM. - CATEGORY CWZ
Rating : 600/1000V

End of page
