



SIRIM QAS INTERNATIONAL SDN. BHD.

(No. Syarikat 199601037981(410334-X))

1, Persiaran Dato' Menteri, Seksyen 2, Peti Surat 7035, 40700 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel : 603-5544 6400 Emel : cserviceqas@sirim.my www.sirim-qas.com.my

File No : P5-015766
Licence No : PC005454

Date : 19/12/2022

TONN CABLE SDN BHD
LOT 1 (PT 54), JALAN PERUSAHAAN 5
KAWASAN PERUSAHAAN BERANANG
43700 BERANANG
SELANGOR, MALAYSIA

Attn : KHOO KHAI SIAN

Tel No : 03-876698888

Fax No : 03-87668111

Dear Sir/Madam,

Product Certification Licence

Product : FLEXIBLE CABLES
Standard : MS 2112-5 : 2009, AMD. 1 : 2017

With regards to your request for new/renewal/changes of licence(s) under the SIRIM Product Certification Licence scheme, enclosed please find the copy of the licence(s) and the certification report(s) for your safe keeping.

For enquiry, please contact

Officer Name : MUHAMAD ZULHANIZAM BIN IBRAHIM
Contact No : 603-55445191
Email : hanizam@sirim.my

Thank you.

This is a computer generated document. No signature is required.

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM

SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to

TONN CABLE SDN BHD
LOT 1 (PT 54), JALAN PERUSAHAAN 5
KAWASAN PERUSAHAAN BERANANG
43700 BERANANG
SELANGOR, MALAYSIA

Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on

FLEXIBLE CABLES

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan
as complying with

MS 2112-5 : 2009, AMD. 1 : 2017



Nur Fadhilah binti Muhammad
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.



SCHEDULE

TONN CABLE SDN BHD



Trade Mark : TONN CABLE
Model : LIGHT PVC SHEATHED, FLEXIBLE CABLE, PLAIN ANNEALED COPPER CLASS 5 MAXIMUM TEMPERATURE 70°C
Rating : 300/300V
Type : MS VVF 20
Size : 2-CORE, 3 CORE (0.5,0.75)mm²

Trade Mark : TONN CABLE
Model : ORDINARY PVC SHEATHED, FLEXIBLE CABLE, PLAIN ANNEALED COPPER CLASS 5 MAXIMUM TEMPERATURE 70°C
Rating : 300/500V
Type : MS VVF 21
Size : 2 CORE, 3 CORE, 4 CORE, 5 CORE (0.75, 1, 1.25,1.5,2.5,4)mm²

End of page
