



## SIRIM QAS INTERNATIONAL SDN. BHD.

(No. Syarikat 199601037981(410334-X))

1, Persiaran Dato' Menteri, Seksyen 2, Peti Surat 7035, 40700 Shah Alam, Selangor Darul Ehsan, Malaysia  
Tel : 603-5544 6400 Emel : cserviceqas@sirim.my www.sirim-qas.com.my

File No : P5-004534  
Licence No : PT049508

Date : 12/12/2023

TONN CABLE SDN BHD  
LOT 1 (PT 54), JALAN PERUSAHAAN 5  
KAWASAN PERUSAHAAN BERANANG  
43700 BERANANG  
SELANGOR, MALAYSIA

Attn : MR. KHOO KHAI SIAN

Tel No : 03-87669888

Fax No : 03-87668111

Dear Sir/Madam,

### **Product Certification Licence**

Product : FLAME RETARDANT CABLES - CATEGORY C  
Standard : IEC 60332-3-24 : 2009

---

With regards to your request for new/renewal/changes of licence(s) under the SIRIM Product Certification Licence scheme, enclosed please find the copy of the licence(s) and the certification report(s) for your safe keeping.

For enquiry, please contact

Officer Name : MUHAMMAD AZHAR MD. ARIS  
Contact No : 603-55446415  
Email : azharma@sirim.my

Thank you.

*This is a computer generated document. No signature is required.*

# LESEN PENSIJILAN BARANGAN

## *Product Certification Licence*



SIRIM

**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada**  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

**TONN CABLE SDN BHD  
LOT 1 (PT 54), JALAN PERUSAHAAN 5  
KAWASAN PERUSAHAAN BERANANG  
43700 BERANANG  
SELANGOR, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan**  
*a licence to use the Certification Mark on*

**FLAME RETARDANT CABLES - CATEGORY C**

**Please refer to detail in the SCHEDULE**

**sebagai mematuhi keperluan**  
*as complying with*

**IEC 60332-3-24 : 2009**



**Nur Fadhilah binti Muhammad**  
Ketua Pegawai Eksekutif  
*Chief Executive Officer*  
SIRIM QAS International Sdn. Bhd.



# SCHEDULE

## TONN CABLE SDN BHD



**SIRIM**

|            |   |
|------------|---|
| Trade Mark | : TONN CABLE  |
| Model      | : MICA-LAYERED, MINERAL FILLED LSHF INSULATED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10) SQ. MM.  |
| Rating     | : 600/1000V   |
| Trade Mark | : TONN CABLE  |
| Model      | : MICA-LAYERED, XLPE-INSULATED, PVC-SHEATHED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630) SQ. MM.                                   |
| Rating     | : 600/1000V   |
| Trade Mark | : TONN CABLE  |
| Model      | : MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF-SHEATHED, NON-ARMOURED, SINGLE-CORE, STRANDED CIRCULAR PLAIN ANNEALED COPPER CONDUCTOR (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630) SQ. MM. |
| Rating     | : 600/1000V   |
| Trade Mark | : TONN CABLE  |
| Model      | : MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF SHEATHED, NON-ARMOURED, STRANDED PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM.                   |
| Rating     | : 600/1000V   |
| Trade Mark | : TONN CABLE  |
| Model      | : MICA-LAYERED, MINERAL FILLED XL-LSHF INSULATED, MINERAL FILLED LSHF SHEATHED, ARMOURED, STRANDED PLAIN ANNEALED COPPER CONDUCTOR. 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240) SQ. MM.                       |
| Rating     | : 600/1000V   |

**End of page**