



XLPE INSULATED, PVC SHEATHED CABLES (AI) ARMOURED CABLES



AI / XLPE / SWA / PVC - 3 CORES

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Diameter of steel wire	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	mm	kg/km
16	7/1.70	0.7	1.25	1.8	22.6	865
25	7/2.14	0.9	1.6	1.8	26.7	1280
35	19/1.53	0.9	1.6	1.8	26.0	1500
50	19/1.78	1.0	1.6	1.8	29.2	1640
70	19/2.14	1.1	2.0	2.0	34.2	2315
95	19/2.52	1.1	2.0	2.2	37.6	2780
120	37/2.03	1.2	2.0	2.3	42.9	3230
150	37/2.25	1.4	2.5	2.5	49.1	4250
185	37/2.52	1.6	2.5	2.6	50.6	4915
240	61/2.25	1.7	2.5	2.8	58.0	5980
300	61/2.52	1.8	2.5	3.0	61.7	6960
400	61/2.85	2.0	2.5	3.2	66.5	8350



AI / XLPE / SWA / PVC - 4 CORES

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Diameter of steel wire	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	mm	kg/km
16	7/1.70	0.7	1.6	1.8	25.1	1130
25	7/2.14	0.9	1.6	1.8	28.9	1479
35	19/1.53	0.9	1.6	1.9	29.8	1762
50	19/1.78	1.0	1.6	2.0	33.4	2010
70	19/2.14	1.1	2.0	2.2	39.0	2835
95	19/2.52	1.1	2.0	2.3	42.3	3430
120	37/2.03	1.2	2.5	2.5	47.8	4510
150	37/2.25	1.4	2.0	2.6	52.6	5180
185	37/2.52	1.6	2.5	2.8	56.1	6150
240	61/2.25	1.7	2.5	3.0	64.2	7460
300	61/2.52	1.8	2.5	3.2	70.5	8740
400	61/2.85	2.0	3.15	3.5	79.0	11540