


PVC INSULATED, PVC SHEATHED CABLES (NON-ARMOURED)



Cu / PVC / PVC - 2 Cores

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	kg/km
MS 2112-4 / MS 136 / BS 6004 300 / 500 V					
1.5	7/0.53	0.7	1.2	8.4	110
2.5	7/0.67	0.8	1.2	9.6	140
4	7/0.85	0.8	1.2	10.6	200
6	7/1.04	0.8	1.2	12.0	260
10	7/1.35	1.0	1.4	15.2	410
16	7/1.70	1.0	1.4	17.2	550
25	7/2.14	1.2	1.4	20.3	840
35	19/1.53	1.2	1.6	18.8	900
MS 2102 / IEC 60502-1 600 / 1000 V					
1.5	7/0.53	0.8	1.8	10.2	140
2.5	7/0.67	0.8	1.8	11.0	176
4	7/0.85	1.0	1.8	12.9	251
6	7/1.04	1.0	1.8	14.3	279
MS 2102 / MS 274 / BS 6346 / IEC 60502-1 600 / 1000 V					
10	7/1.35	1.0	1.8	16.0	440
16	7/1.70	1.0	1.8	18.0	580
25	7/2.14	1.2	1.8	21.1	880
35	19/1.53	1.2	1.8	19.2	920
50	19/1.78	1.4	1.8	21.6	1250
70	19/2.14	1.4	1.9	24.3	1670
95	19/2.52	1.6	2.0	27.8	2270
120	37/2.03	1.6	2.1	30.2	2850
150	37/2.25	1.8	2.2	33.2	3410
185	37/2.52	2.0	2.4	36.9	4270
240	61/2.25	2.2	2.5/2.6*	41.5	5550
300	61/2.52	2.4	2.7	45.9	7000
400	61/2.85	2.6	2.9/3.0*	51.1	8880

* Value specified in MS 2102 & IEC 60502-1