


Product Specification

XLPE INSULATED, PVC SHEATHED CABLES (NON-ARMOURED)



Cu / XLPE / PVC - 2 Cores

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	kg/km
IEC 60502-1 / BS 5467 / MS 2106 600 / 1000 V					
1.5	7/0.53	0.7	1.8	9.8	130
2.5	7/0.67	0.7	1.8	10.6	155
4	7/0.85	0.7	1.8	11.6	194
6	7/1.04	0.7	1.8	13.3	255
10	7/1.35	0.7	1.8	14.9	365
16	7/1.70	0.7	1.8	17.0	490
25	7/2.14	0.9	1.8	20.2	655
35	19/1.53	0.9	1.8	17.8	840
50	19/1.78	1.0	1.8	19.9	1120
70	19/2.14	1.1	1.8	22.7	1545
95	19/2.52	1.1	2.0	25.7	2050
120	37/2.03	1.2	2.1	28.4	2570
150	37/2.25	1.4	2.2	31.4	3150
185	37/2.52	1.6	2.3	34.9	3950
240	61/2.25	1.7	2.5	39.1	5130
300	61/2.52	1.8	2.7	43.1	6340
400	61/2.85	2.0	2.9	48.3	8120