


Product Specification

XLPE INSULATED, PVC SHEATHED CABLES (NON-ARMOURED)



Cu / XLPE / PVC - 3 Cores

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	kg/km
IEC 60502-1 / BS 5467 / MS 2106 600 / 1000 V					
1.5	7/0.53	0.7	1.8	10.3	145
2.5	7/0.67	0.7	1.8	11.2	185
4	7/0.85	0.7	1.8	12.3	243
6	7/1.04	0.7	1.8	14.0	320
10	7/1.35	0.7	1.8	15.8	470
16	7/1.70	0.7	1.8	18.1	643
25	7/2.14	0.9	1.8	21.5	930
35	19/1.53	0.9	1.8	20.8	1230
50	19/1.78	1.0	1.8	23.8	1610
70	19/2.14	1.1	1.9	27.6	2280
95	19/2.52	1.1	2.0	30.8	3090
120	37/2.03	1.2	2.1	36.1	3880
150	37/2.25	1.4	2.3	40.9	4770
185	37/2.52	1.6	2.4	43.5	5950
240	61/2.25	1.7	2.6	49.4	7805
300	61/2.52	1.8	2.8	53.1	9680
400	61/2.85	2.0	3.1	58.1	12200